


PRODUCT SPECIFICATION

- Product : **F-LOR**
- Housing : High quality cold-rolled steel sheet
of thickness 0.6 (t6) or 0.8mm (t8)
- Reflector : 99.85% high purity anodized aluminium reflector
with total reflectance of 87% (87) mirror finished
(din5036-2) for normal usage. optional:
tr=95% (95) for high efficiency purpose
- Louver : 99.85% high purity anodized aluminium louver
with total reflectance of 87% mirror finished
(din 5036-2) for longitudinal with aluminium profile
to anti-glare. standard 5 blades for 18w and 10
blades for 36w with spring-lock type for ease of
maintenance.
- Installation : For recessed t-bar and gypsum ceiling installation
- IP : 20



Dimension

Model No.	Watt	Dimension (mm.)					Cut Out (mm.)
		L1	L2	W1	W2	H	
F-LOR118	1 X T8 18W.	595	620	200	170	80	575 X 185
F-LOR118/30	1 X T8 18W.	595	620	295	265	80	575 X 275
F-LOR218	2 X T8 18W.	595	620	295	265	80	575 X 275
F-LOR218/60	2 X T8 18W.	595	620	595	565	80	575 X 575
F-LOR318	3 X T8 18W.	595	620	595	565	80	575 X 575
F-LOR418	4 X T8 18W.	595	620	595	565	80	575 X 575
F-LOR136	1 X T8 36W.	1195	1222	200	170	80	1175 X 185
F-LOR136/30	1 X T8 36W.	1195	1222	295	265	80	1175 X 275
F-LOR236	2 X T8 36W.	1195	1222	295	265	80	1175 X 275
F-LOR236/60	2 X T8 36W.	1195	1222	595	565	80	1175 X 575
F-LOR336	3 X T8 36W.	1195	1222	595	565	80	1175 X 575
F-LOR436	4 X T8 36W.	1195	1222	595	565	80	1175 X 575

Led Fluorescent T8 Lamp for Luminaire

