


## PRODUCT SPECIFICATION

- Product : **F-LOS**
- Housing : High quality cold-rolled steel sheet  
of thickness 0.6 (t6) or 0.8mm (t8)
- Reflector : 99.85% high purity anodized aluminium reflector  
with total reflectance of 87% (87) mirror finished  
(din 5036-2) for normal usage. optional:  
tr=95% (95) for high efficiency purpose
- Louver : 99.85% high purity anodized aluminium louver  
with total reflectance of 87% mirror finished  
(din 5036-2) for longitudinal with aluminium profile  
to anti-glare. standard 5 blades for 18w and 10  
blades for 36w with spring-lock type for ease of  
maintenance.
- Installation : For surface mounted or suspension rod installation
- IP : 20



### Dimension

| Model No.   | Watt        | Dimension (mm.) |     |    |
|-------------|-------------|-----------------|-----|----|
|             |             | L1              | L2  | H  |
| F-LOS118    | 1 X T8 18W. | 615             | 200 | 80 |
| F-LOS118/30 | 1 X T8 18W. | 615             | 295 | 80 |
| F-LOS218    | 2 X T8 18W. | 615             | 295 | 80 |
| F-LOS218/60 | 2 X T8 18W. | 615             | 595 | 80 |
| F-LOS318    | 3 X T8 18W. | 615             | 595 | 80 |
| F-LOS418    | 4 X T8 18W. | 615             | 595 | 80 |
| F-LOS136    | 1 X T8 36W. | 1222            | 200 | 80 |
| F-LOS136/30 | 1 X T8 36W. | 1222            | 295 | 80 |
| F-LOS236    | 2 X T8 36W. | 1222            | 295 | 80 |
| F-LOS236/60 | 2 X T8 36W. | 1222            | 595 | 80 |
| F-LOS336    | 3 X T8 36W. | 1222            | 595 | 80 |
| F-LOS436    | 4 X T8 36W. | 1222            | 595 | 80 |

### Led Fluorescent T8 Lamp for Luminaire

