


PRODUCT SPECIFICATION

- Product : **F-LORP-1**
- Housing : High quality cold-rolled steel sheet of thickness 0.6 (t6) or 0.8mm (t8)
- Reflector : 99.85% high purity anodized aluminium reflector with total reflectance of 87% (87) mirror finished (din 5036-2) for normal usage. optional: tr=95% (95) for high efficiency purpose
- Diffuser : High quality acrylic diffuser with steel painted frame.
four acrylic diffusers are available
: prismatic (p) , opal (m) , stipple (o) and clear (j) with spring-lock type frame for ease of maintenance.
- Installation : For recessed t-bar and gypsum ceiling installation
IP : 20



Prismatic



Opal





Clear



Stipple

Dimension

Model No.	Watt	Diamention (mm.)					Cut Out (mm.)
		L1	L2	W1	W2	H	
F-LORP-1 118	1 X T8 18W.	595	620	200	170	80	575 X 185
F-LORP-1 118/30	1 X T8 18W.	595	620	295	265	80	575 X 275
F-LORP-1 218	2 X T8 18W.	595	620	295	265	80	575 X 275
F-LORP-1 218/60	2 X T8 18W.	595	620	595	565	80	575 X 575
F-LORP-1 318	3 X T8 18W.	595	620	595	565	80	575 X 575
F-LORP-1 418	4 X T8 18W.	595	620	595	565	80	575 X 575
F-LORP-1 136	1 X T8 36W.	1195	1222	200	170	80	1175 X 185
F-LORP-1 136/30	1 X T8 36W.	1195	1222	295	265	80	1175 X 275
F-LORP-1 236	2 X T8 36W.	1195	1222	295	265	80	1175 X 275
F-LORP-1 236/60	2 X T8 36W.	1195	1222	595	565	80	1175 X 575
F-LORP-1 336	3 X T8 36W.	1195	1222	595	565	80	1175 X 575
F-LORP-1 436	4 X T8 36W.	1195	1222	595	565	80	1175 X 575



Led Fluorescent T8 Lamp for Luminaire

