


PRODUCT SPECIFICATION

- Product : **F-LOSP**
- Housing : High quality cold-rolled steel sheet of thickness 0.6 (t6) or 0.8mm (t8)
- Reflector : 99.85% high purity anodized aluminium reflector with total reflectance of 87% (87) mirror finished (din 5036-2) for normal usage. optional: tr=95% (95) for high efficiency purpose
- Diffuser : High quality acrylic diffuser with steel painted frame.
four acrylic diffusers are available
: prismatic (p) , opal (m) , stipple (o) and clear (j) with spring-lock type frame for ease of maintenance.
- Installation : For surface mounted or suspension rod installation.
IP : 20



Prismatic



Opal





Clear



Stipple

Dimension

Model No.	Watt	Dimension (mm.)		
		L1	L2	H
F-LOSP118	1 X T8 18W.	615	200	82
F-LOSP118/30	1 X T8 18W.	615	295	82
F-LOSP218	2 X T8 18W.	615	295	82
F-LOSP218/60	2 X T8 18W.	615	595	82
F-LOSP318	3 X T8 18W.	615	595	82
F-LOSP418	4 X T8 18W.	615	595	82
F-LOSP136	1 X T8 36W.	1222	200	82
F-LOSP136/30	1 X T8 36W.	1222	295	82
F-LOSP236	2 X T8 36W.	1222	295	82
F-LOSP236/60	2 X T8 36W.	1222	595	82
F-LOSP336	3 X T8 36W.	1222	595	82
F-LOSP436	4 X T8 36W.	1222	595	82



Led Fluorescent T8 Lamp for Luminaire

