

PRODUCT SPECIFICATION

Product : F-LORPQ (T8 Recess T-bar clean room luminaire)

Housing : High quality cold-rolled steel sheet of thickness 0.6 (t6) or 0.8mm (t8)

Reflector : 99.85% high purity anodized aluminium reflector with total reflectance of 87% (87) mirror finished (din 5036-2) for normal usage. optional: tr=95% (95) for high efficiency purpose

Diffuser : High quality acrylic diffuser with steel painted frame. four acrylic diffusers are available : prismatic (p) , opal (m) , stipple (o) and clear (j) with spring-lock type frame for ease of maintenance.

Installation : For recessed t-bar and gypsum ceiling installation

IP : 54



Prismatic



Opal




Clear




Stipple

Dimension



FRONT VIEW



SIDE VIEW

Model No.	Watt	Diamension (mm.)					Cut Out (mm.)
		L1	L2	W1	W2	H	
F-LORPQ118	1 X T8 18W.	595	620	200	170	100	575 X 185
F-LORPQ118/30	1 X T8 18W.	595	620	295	265	100	575 X 275
F-LORPQ218	2 X T8 18W.	595	620	295	265	100	575 X 275
F-LORPQ218/60	2 X T8 18W.	595	620	595	565	100	575 X 575
F-LORPQ318	3 X T8 18W.	595	620	595	565	100	575 X 575
F-LORPQ418	4 X T8 18W.	595	620	595	565	100	575 X 575
F-LORPQ136	1 X T8 36W.	1195	1222	200	170	100	1175 X 185
F-LORPQ136/30	1 X T8 36W.	1195	1222	295	265	100	1175 X 275
F-LORPQ236	2 X T8 36W.	1195	1222	295	265	100	1175 X 275
F-LORPQ236/60	2 X T8 36W.	1195	1222	595	565	100	1175 X 575
F-LORPQ336	3 X T8 36W.	1195	1222	595	565	100	1175 X 575
F-LORPQ436	4 X T8 36W.	1195	1222	595	565	100	1175 X 575

Led Fluorescent T8 Lamp for Luminaire

