


PRODUCT SPECIFICATION

- Product : **F-LORP**
- Housing : High quality cold-rolled steel sheet
of thickness 0.6 (t6) or 0.8mm (t8)
- Reflector : 99.85% high purity anodized aluminium reflector
with total reflectance of 87% (87) mirror finished
(din 5036-2) for normal usage. optional:
tr=95% (95) for high efficiency purpose
- Diffuser : High quality acrylic diffuser with steel painted frame.
four acrylic diffusers are available
: prismatic (p) , opal (m) , stipple (o) and clear (j) with
spring-lock type frame for ease of maintenance.
- Installation : For recessed t-bar and gypsum ceiling installation
IP : 20



Prismatic



Opal




Clear



Stipple

Dimension

Model No.	Watt	Diamention (mm.)					Cut Out (mm.)
		L1	L2	W1	W2	H	
F-LORP118	1 X T8 18W.	595	620	200	170	100	575 X 185
F-LORP118/30	1 X T8 18W.	595	620	295	265	100	575 X 275
F-LORP218	2 X T8 18W.	595	620	295	265	100	575 X 275
F-LORP218/60	2 X T8 18W.	595	620	595	565	100	575 X 575
F-LORP318	3 X T8 18W.	595	620	595	565	100	575 X 575
F-LORP418	4 X T8 18W.	595	620	595	565	100	575 X 575
F-LORP136	1 X T8 36W.	1195	1222	200	170	100	1175 X 185
F-LORP136/30	1 X T8 36W.	1195	1222	295	265	100	1175 X 275
F-LORP236	2 X T8 36W.	1195	1222	295	265	100	1175 X 275
F-LORP236/60	2 X T8 36W.	1195	1222	595	565	100	1175 X 575
F-LORP336	3 X T8 36W.	1195	1222	595	565	100	1175 X 575
F-LORP436	4 X T8 36W.	1195	1222	595	565	100	1175 X 575



Led Fluorescent T8 Lamp for Luminaire

